

AMENDMENTS TO THE SPECIFICATION

Included below are amendments being made to the specification. No new matter has been added. A substitute specification including all amendments is submitted herewith.

Please insert the below paragraphs prior to paragraph [0001]:

BACKGROUND

Onychomycosis is a fungal infection of a nail, commonly a human nail. The condition can be caused by a fungus, such as dermatophytes, yeast, or mould. The fungus can invade the nail plate or nail bed, potentially causing the nail to separate from the nail bed, a thickening of the nail, discoloration, and other adverse symptoms. A convenient treatment for onychomycosis is needed that is both fast and safe for a care provider.

SUMMARY

Provided are devices and methods for treating onychomycosis. In a first embodiment, an ultraviolet (UV) light source is directed at an infected area, a device detects whether a hand of the user is an adult hand, and if so, the light source is powered on. The light source may be powered off after the passage of a predetermined amount of time.

In another embodiment, a device is provided for treating onychomycosis. The device may include a UV light source, a UV transmissive cover for the light source, a safety sensor for preventing powering on of the light source unless the user is an adult, and a power source for the light source. The device may also include a ballast circuitry and/or a timing circuitry.

BRIEF DESCRIPTION OF THE FIGURES

Figure 1 depicts an example of a portable handheld germicidal system.

Figure 2 is a flow chart depicting an example of a method for treating onychomycosis.

DETAILED DESCRIPTION

Please replace paragraph [0001] with the following amended paragraph:

~~[Para 1] Figure #1~~ FIG. 1 illustrates an example of a portable hand-held germicidal system, device 101 which may be pen light sized. ~~For Such a device may be used in conjunction with~~ a method of treating onychomycosis of the human nail. ~~#1 Handheld germicidal device 101 may be used to treat fungal infection of the nail 120, defined as the nail matrix, bed or plate.~~

Please replace paragraph [0002] with the following amended paragraph:

~~[Para 2] The system includes extending~~ The device 101 may include a pen light sized quartz UV lamp 103 that emits light in the germicidal range extending from a first end ~~#2 102, a pen light size quartz UV lamp #3 that emits light in the germicidal range.~~ In the ~~exemplary one~~ embodiment of the device 101, ~~system~~ the lamp #3 emits light at ~~having a wavelength of 254 nanometers (nm).~~ The lamp is ~~may be~~ powered ~~through via~~ ballast circuitry ~~#4 104~~ by a battery ~~#5 105~~ which ~~in the example system is include~~ four AA batteries ~~in this embodiment.~~ A quartz cover ~~#6 106~~ surrounding the UV lamp ~~#3 103~~ fits into a holder ~~#7 107~~ that also acts as a shock absorber for the lamp ~~#2 103~~. The holder ~~#7 107~~ ~~will may~~ compresses and bend as appropriate, should the cover ~~#2 106~~ and the lamp ~~#3 103~~ be bumped or jarred ~~within reason.~~ A plastic UV filter ~~#8 108~~ may be securely mounted to ~~only one side of the pen device 101 is used.~~ The UV filter 108 may be made of plastic and ~~may serve to shield the user's eyes from potentially harmful levels of the UV rays.~~ The device 101, may also include an additional reflective cover (not shown) which may be used to reflect and direct the UV light.

Please replace paragraph [0003] with the following amended paragraph:

~~[Para 3] An adult~~ Adult hand safety sensors ~~#10 110~~ may be ~~which is~~ incorporated into the germicidal device 101. Sensors 110a and 110b work with ~~in~~ a continuity sensor circuit ~~#4 111~~ which may prevent the UV lamp from turning on until the unit is firmly gripped by the hand of an adult. Continuity sensor circuit 111 may be located anywhere is ~~connected to switches #4 between the UV lamp #3 103, and the ballast circuitry #4 104, and~~

~~the batteries 105.#5 prevents the UV lamp from turning on until the unit is firmly gripped by an adults hand.~~ Sensors 110 may include, for example, capacitive-type sensors that sense the difference in capacitance of a moist adult hand versus the surrounding air. When the continuity sensor circuit 111 determines that device 101 is firmly gripped, it may be assumed that the hand is an adult hand because, in part, of the relative locations of sensors 110a and 110b. Sensor circuit 111 may then allow the lamp 103 to be turned on. Germicidal device 101 may also include timing circuitry 112 which may power off lamp 103 after the passage of a predetermined amount of time.

Please delete paragraphs [0004] and [0005]:

~~[Para 4] The plastic UV filter #8 protects the user who is holding the device #1 from harmful levels of the UV radiation, which might otherwise adversely affect his or her eyes.~~

~~[Para 5] The sensor #10 may, for example, be a capacitive type sensor that senses the difference in capacitance of the moist adult hand and the surrounding air. When the sensor determines that it is firmly gripped, which necessarily means that the unit #1 is firmly gripped by an adults hand, the sensor closes the switches and allows the lamp to be turned on.~~

Please insert the below paragraphs following new paragraph [0005]:

FIG. 2 is a flowchart depicting an example of a process 200 for treating onychomycosis. At operation 201, a device 101 comprising a UV light source 103 and associated UV transmissive cover 106 is directed at an area of a body to be disinfected, such as a human toe nail. At operation 202, the device senses whether it is being held by an adult. At decision 203, if the device 101 is held by an adult, then at operation 204, the light source 103 is activated, emitting UV radiation having a wavelength in the range of, for example, 254 nm, disinfecting the area of the body. At operation 205, the light source 103 may be automatically powered off after the passage of a certain predetermined amount of time.

Please delete the Abstract and replace it with the following Abstract:

A handheld ultraviolet germicidal device is used for the treatment of nail fungus. A UV lamp is protected by a transmissive quartz cover. The UV lamp may include a battery-powered ballast circuitry, and may incorporate a timing circuit. A continuity sensor circuit may also be used to ensure that the device is used only by adults. A method can be used, where the UV lamp is directed at an infected human nail, and where the lamp is powered on only after the continuity sensor circuit determines that the user is likely an adult.